


1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** 4CR 5120 1K PU-Scheibenkleber
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Adhesives
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
4CR Vertriebsgesellschaft mbH
Donaustraße 2
94469 Deggendorf
Tel.: +49 (0) 4841/665015
Fax: +49 (0) 4841/665016
e-Mail: 4cr@b2bmail.eu
- **Emergency telephone number:** +49(0)700 24112112 (MIP)

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 Xn; Sensitising
R42: May cause sensitisation by inhalation.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xn Harmful
- **Hazard-determining components of labelling:**
4,4'-methylenediphenyl diisocyanate
methylenediphenyl diisocyanate
- **Risk phrases:**
42 May cause sensitisation by inhalation.
- **Safety phrases:**
2 Keep out of the reach of children.
13 Keep away from food, drink and animal feedingstuffs.
23 Do not breathe vapour.
36 Wear suitable protective clothing.
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.
- **Special labelling of certain preparations:**
Contains isocyanates. See information supplied by the manufacturer
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 1)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 28553-12-0 EINECS: 249-079-5	di-"isononyl" phthalate	10-25%
CAS: 101-68-8 EINECS: 202-966-0	4,4'-methylenediphenyl diisocyanate ☒ Xn R20-40-48; ☒ Xn R42/43; ☒ Xi R36/37/38 ⚠ Resp. Sens. 1, H334; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≤ 1.0%
CAS: 26447-40-5 EINECS: 247-714-0	methylenediphenyl diisocyanate ☒ Xn R20-40-48; ☒ Xn R42/43; ☒ Xi R36/37/38 ⚠ Resp. Sens. 1, H334; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≤ 1.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Hydrogen cyanide (HCN)
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 2)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water	45 Vol.%
ethanol or isopropanol	50 Vol.%
ammonia solution (Density= 0.88)	5 Vol.%

- alternatively (non-flammable):

sodium carbonate	5 Vol.%
water	95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

· **Information about fire - and explosion protection:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:**

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Store away from foodstuffs.

· **Further information about storage conditions:**

Store in dry conditions.

Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

· **Storage class:** 10

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

28553-12-0 di-"isononyl" phthalate

WEL () Long-term value: 5 mg/m³

101-68-8 4,4'-methylenediphenyl diisocyanate

WEL () Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

(Contd. on page 4)

Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 3)

- **Additional information:** *The lists valid during the making were used as basis.*
- **Exposure controls**
- **Personal protective equipment:**
All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.
- **General protective and hygienic measures:**
*Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.*
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**
*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** *Goggles recommended during refilling*

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100°C
- **Flash point:** Not applicable.
- **Ignition temperature:** 420°C (DIN 51794)
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**

Lower:	0.1 Vol %
Upper:	0.2 Vol %

(Contd. on page 5)

Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 4)

· Vapour pressure at 20°C:	23 hPa
· Density at 20°C:	1.36 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Water:	43.7 %
· Solids content (weight-%):	56.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Possible in traces.
Nitrogen oxides
Hydrogen chloride (HCl)
Hydrogen cyanide (prussic acid)
Carbon monoxide
Nitrogen oxides (NO_x)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral | LD50 | 2200 mg/kg (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through inhalation.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

(Contd. on page 6)

Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 5)

- **Sensitisation** May cause sensitisation by inhalation.

12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|----------|---|
| 08 04 10 | waste adhesives and sealants other than those mentioned in 08 04 09 |
|----------|---|
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -
- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No
- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**

· **Information about limitation of use:**

101-68-8	4,4'-methylenediphenyl diisocyanate	4
----------	-------------------------------------	---

(Contd. on page 7)



Trade name: 4CR 5120 1K PU-Scheibenkleber

(Contd. of page 6)

Class	Share in %
I	≤ 2,5

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- R20 Harmful by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R40 Limited evidence of a carcinogenic effect.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R48 Danger of serious damage to health by prolonged exposure.

· **Department issuing MSDS:** Laboratory

· * **Data compared to the previous version altered.**