

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **4CR 5400 Steinschlagschutz weiß**
- **Application of the substance / the preparation** Protective coating
- **Manufacturer/Supplier:**
4CR Vertriebsgesellschaft mbH
Donaustraße 2
94469 Deggendorf
Tel.: +49 (0) 4841/665015
Fax: +49 (0) 4841/665016
e-Mail: 4cr@b2bmail.eu
- **Information in case of emergency:** +49(0)700 24112112 (MIP)

2 Hazards identification

- **Hazard description:**



Xn Harmful
F Highly flammable
N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

R 11 Highly flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn, Xi, F, N; R 11-38-51/53-65-66-67	25-50%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Xi, F; R 11-36-66-67	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, Xi, N; R 10-37-51/53-65-66-67	2.5-10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol F; R 11	2.5-10%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Xn, N; R 10-51/53-65-66-67	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 2)

Trade name: 4CR 5400 Steinschlagschutz weiß

(Contd. of page 1)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL ()	Short-term value: 400 ppm Long-term value: 200 ppm
--------	---

64-17-5 ethanol

WEL ()	Long-term value: 1920 mg/m ³ , 1000 ppm
--------	--

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 3)

Trade name: 4CR 5400 Steinschlagschutz weiß

(Contd. of page 2)

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 77°C

· **Flash point:** -10°C (DIN 53213)

· **Ignition temperature:** 287°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 4)

Trade name: 4CR 5400 Steinschlagschutz weiß

(Contd. of page 3)

· Explosion limits:	
Lower:	0.8 Vol %
Upper:	6.0 Vol %
· Vapour pressure at 20°C:	97 hPa
· Density at 20°C:	1.026 g/cm ³ (DIN 53217)
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic at 20°C:	683 mPas
· Solvent separation test:	< 3 %
· Solvent content:	
Organic solvents:	53.3 %
VOC (EC)	546.9 g/l
· Solids content (weight-%):	46.7 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous decomposition products:** Carbon monoxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Ecotoxicological effects:**

- **Aquatic toxicity:**

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 | >1000 mg/kg (bacteria)

- **Remark:** Toxic for fish

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 5)

Trade name: 4CR 5400 Steinschlagschutz weiß

(Contd. of page 4)

Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1139
- **Packaging group:** II
- **Hazard label:** 3
- **Special marking:** Symbol (fish and tree)
- **Description of goods:** 1139 COATING SOLUTION, special provision 640D

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1139
- **Label:** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** Yes
Symbol (fish and tree)
- **Proper shipping name:** COATING SOLUTION

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1139
- **Label:** 3

(Contd. on page 6)

Trade name: 4CR 5400 Steinschlagschutz weiß

(Contd. of page 5)

- **Packaging group:** II
- **Proper shipping name:** COATING SOLUTION
- **Environmental hazards:** Product contains environmentally hazardous substances: Naphtha, aliphatic

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xn Harmful
F Highly flammable
N Dangerous for the environment
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrotreated light
- **Risk phrases:**
11 Highly flammable.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
13 Keep away from food, drink and animal feedingstuffs.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
46 If swallowed, seek medical advice immediately and show this container or label.
- **National regulations:**

· **Information about limitation of use:**

64-17-5 ethanol

5

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
10 Flammable.
11 Highly flammable.
36 Irritating to eyes.
37 Irritating to respiratory system.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.
- **Department issuing MSDS:** Laboratory
- **Contact:** Ingo Bolls