



## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *4CR 7445 Bumper-Paint-Spray schwarz*
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*4CR Vertriebsgesellschaft mbH  
Donaustraße 2  
94469 Deggendorf  
Tel.: +49 (0) 4841/665015  
Fax: +49 (0) 4841/665016  
e-Mail: 4cr@b2bmail.eu*
- **Emergency telephone number:** *+49(0)700 24112112 (MIP)*

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  *Xi; Irritant*
- *R36: Irritating to eyes.*
-  *F+; Extremely flammable*
- *R12: Extremely flammable.*
- *R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.*
- **Information concerning particular hazards for human and environment:**  
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*  
*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.*  
*Warning! Pressurized container.*  
*Has a narcotizing effect.*
- **Classification system:**  
*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*
- **Label elements**
- **Labelling according to EU guidelines:**  
*The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.*
- **Code letter and hazard designation of product:**  
*Xi Irritant*  
*F+ Extremely flammable*
- **Risk phrases:**  
*12 Extremely flammable.*  
*36 Irritating to eyes.*  
*66 Repeated exposure may cause skin dryness or cracking.*  
*67 Vapours may cause drowsiness and dizziness.*
- **Safety phrases:**  
*2 Keep out of the reach of children.*  
*3 Keep in a cool place.*  
*16 Keep away from sources of ignition - No smoking.*  
*23 Do not breathe fumes/aerosol.*

(Contd. on page 2)

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 1)

46 If swallowed, seek medical advice immediately and show this container or label.  
51 Use only in well-ventilated areas.

**Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Xi R36 R10 Flam. Liq. 3, H226; Eye Irrit. 2, H319	≤ 2.5%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn R65; Xi R37; N R51/53 R10-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335+H336	≤ 1.0%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Storage class:** 2B

(Contd. on page 4)

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

WEL ()	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm
	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm

**115-10-6 dimethyl ether**

WEL ()	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 766 mg/m <sup>3</sup> , 400 ppm

**123-86-4 n-butyl acetate**

WEL ()	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL ()	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
Sk	

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

**Form:** Aerosol  
**Colour:** According to product specification

· **Odour:** Characteristic· **Odour threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** -24°C

· **Flash point:** < 0°C (DIN 53213)· **Ignition temperature:** 235°C (DIN 51794)· **Decomposition temperature:** Not determined.· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

**Lower:** 1.2 Vol %  
**Upper:** 18.6 Vol %

· **Vapour pressure at 20°C:** 5200 hPa· **Density at 20°C:** 0.78 g/cm<sup>3</sup> (DIN 53217)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not applicable.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Segregation coefficient (n-octanol/water):** Not determined.· **Viscosity:**

**Dynamic:** Not determined.  
**Kinematic:** Not determined.

· **Solvent content:**

**Organic solvents:** 85.1 %  
**VOC (EC)** 664.6 g/l

· **Solids content (weight-%):** 14.9 %· **Other information** No further relevant information available.

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 5)

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
14 06 03*	other solvents and solvent mixtures
15 01 04	metallic packaging

(Contd. on page 7)

**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **UN proper shipping name:** 1950 AEROSOLS
- **Tunnel restriction code** D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

- **Special precautions for user** Warning: Gases.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**

- **Information about limitation of use:**

112-07-2	2-butoxyethyl acetate	4
----------	-----------------------	---

(Contd. on page 8)



**Trade name: 4CR 7445 Bumper-Paint-Spray schwarz**

(Contd. of page 7)

Class	Share in %
NK	50-100

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H220 *Extremely flammable gas.*
- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H280 *Contains gas under pressure; may explode if heated.*
- H304 *May be fatal if swallowed and enters airways.*
- H319 *Causes serious eye irritation.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H411 *Toxic to aquatic life with long lasting effects.*
- R10 *Flammable.*
- R11 *Highly flammable.*
- R12 *Extremely flammable.*
- R36 *Irritating to eyes.*
- R37 *Irritating to respiratory system.*
- R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R65 *Harmful: may cause lung damage if swallowed.*
- R66 *Repeated exposure may cause skin dryness or cracking.*
- R67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS:** Laboratory

· \* **Data compared to the previous version altered.**