



Art.-No.:6.1171.0355  
 6.1171.0655  
 6.1171.0955  
 6.1171.1255

1171

## Fine Line Tape Orange

### Characteristics

4CR 1171 High Temperature Fine Line Tape uses a thermally stabilized PVC backing with a rubber based pressure sensitive adhesive. This PVC tape will perform in temperatures up to 150°C for at least 30 minutes and leave a sharp, clean separation line. 4CR 1171 adheres to a wide variety of surfaces. It follows contours and remains in place as long as necessary and leaves no residue upon removal.

### Tech Tip

Masking tape for multi colour and design paint jobs. Designed for long straight lines whilst remaining flexible.

### Application

Preferred where tape must conform and follow contours without wrinkling or tearing. 4CR 1171 is used when flake resistance and removal without adhesive transfer is important.

### Technical Data

Carrier	PVC
Colour	Orange
Adhesive	Acrylic (Solvent Based)
Thickness	0.12mm (+/- 0.02mm) ASTM-D-1000
Width	3mm, 6mm, 9mm und 12mm (+/- 1mm)
Length	55m (+/- 0.1m)
Breaking strength	Minimum 20 (N/cm) Typical 23
Elongation strength	Minimum 120 % Typical 160
Heat resistance	150°C for at least 30 minutes