



Art.-No.:6.1173.0355  
 6.1173.0655  
 6.1173.0955  
 6.1173.1255

1173

## Fine Line Tape Olive

### Characteristics

4CR 1173 High Temperature Fine Line Tape uses a thermally stabilized Polypropylene backing with a Urethane based pressure sensitive adhesive. This fine line tape will perform in temperatures up to 138°C for at least 45 minutes and leave a sharp, clean separation line. 4CR 1173 adheres to a wide variety of surfaces. It follows contours and remains in place as long as necessary and leaves no residue upon removal. 4CR 1173 meets military specification T-215955D type III.

### Tech Tip

Rigid tape for multi colour and design paint jobs. Designed for straight line jobs.

### Application

Preferred where tape must conform and follow contours without wrinkling or tearing. 4CR 1173 is used when flake resistance and removal without adhesive transfer is important.

### Technical Data

Carrier	Embossed Polypropylene
Colour	Olive Green
Adhesive	Pigmented Urethane Pressure Sensitive Adhesive
Thickness	0.127mm PSTC-33
Width	3mm, 6mm, 9mm and 12mm (+/- 1mm)
Length	55m (+/- 0.1m)
Tensile strength	0.215 kg/mm ASTM D-3759
Elongation strength	600 %
Adhesion to steel	33.6 g/mm ASTM D-3330
Heat resistance	138°C Maximum for 45 minutes